

38MT+™ Heavy Duty Gear Reduction Starter


FEATURES & BENEFITS

- Available* with Integrated Over Crank Protection
 - (IOCP), a built-in circuit breaker, protects the starter from thermal damage, automatically resetting at a safe operating temperature while eliminating the need for a wiring harness.
- 38MT+ features an Integral Magnetic Switch (IMS). IMS reduces voltage drop and ensures the solenoid receives the maximum available voltage in any starting condition.
- Electrical soft-start consistently and accurately engages the pinion with the ring gear providing increased reliability.
- Warranty: Non-OCP model: 1 year / unlimited miles Integrated OCP model: 3 years / unlimited miles (Applicable to U.S. and Canada only)
- * Part Number 8201084





COMPETITIVE COMPARISON




Cranks up to 4% faster than the competition

Starter Model	ОСР	Faster Cranking	Weight	
Delco Remy 38MT+	Optional	82 Engine RPM	28.44 lbs/12.9kg	
Melco	No	79 Engine RPM	29.32lbs/13.3kg	



38MT+™ Heavy Duty Gear Reduction Starter



SPECIFICATIONS

Engine Size	up to 13 liter		
Rotation	Clockwise		
Mounting	SAE #3		
Pinion Data	12 Tooth, Mod 3-metric		
Output	out 4.3kW peak at 12V		
Weight	12.9 kg/28.44 lbs		
Diameter	ameter 100 mm/3.94 inches		
Heavy Duty Drive	Electrical Soft-Start, Engagement System, Overrunning Clutch		

38MT+designed to fit MX 11 and 13 liter engines

ОЕМ	Engine	Non-OCP 38MT+	Integrated OCP 38MT+	Teeth/Pinion/Pitch	Melco
PACCAR	MX 11/13	8200977	8201084	12 Tooth, Mod 3 Metric	D61-1003-001 D61-6002-011 M009T72578 M9T72578 PC2578 1847916

Tech Support 800-372-3555

If you need assistance with part number identification or electrical system troubleshooting, we're here to help.

delcoremy.com

